

```
package fi.paatti.paattidatabaseutils.dbobjects;
```

```
/**  
 * A class for holding TaskData.  
 *  
 * @author Lauri Satokangas, lauri.n.satokangas@student.jyu.fi  
 * @since 0.0.4  
 */  
  
public class TaskData {  
  
    private Object choiceID;  
    private Object choiceSequence;  
  
    /**  
     * Constructor.  
     *  
     * @param choiceID The ID of the taken choice.  
     * @param choiceSequence The sequence number of the choice.  
     */  
  
    public TaskData(Object choiceID, Object choiceSequence) {  
        this.choiceID = choiceID;  
        this.choiceSequence = choiceSequence;  
    }  
  
    /**  
     * Returns the value of choiceID.  
     *  
     * @return the value of choiceID.  
     */  
    public Object getChoiceID() {  
        return choiceID;  
    }  
  
    /**  
     * Sets the value of choiceID.  
     *  
     * @param choiceID new value of choiceID.  
     */  
    public void setChoiceID(Object choiceID) {  
        this.choiceID = choiceID;  
    }  
  
    /**  
     * Returns the value of choiceSequence.  
     */
```

```
* @return choiceSequence the value of choiceSequence.  
 */  
public Object getChoiceSequence() {  
    return choiceSequence;  
}  
  
/**  
 * Sets the value of choiceSequence.  
 * @param choiceSequence new value of choiceSequence.  
 */  
public void setChoiceSequence(Object choiceSequence) {  
    this.choiceSequence = choiceSequence;  
}
```